

REGUPOL® AKTIVPRO™

MODULAR SPORTS & FITNESS SURFACES



33 KEYSTONE DRIVE
LEBANON, PA 17042

P: 1-800-537-8737

F: 717-675-2199

www.regupol.com



REGUPOL® AKTIVPRO™ TILE REVOLUTIONIZING SPORTS & FITNESS SURFACES

The inventor of recycled rubber flooring has unleashed a whole new monster. AKTIVPRO is a patent-pending, modular tile with a dual personality. Its extra-thick, unique composite structure is super durable with outstanding wear resistance. And its revolutionary proprietary inner layer gives this hulk of a product a beast-like quality. AktivPro's beauty is its brilliant color and cushioned comfort, offering a safe, secure solution for tough environments. Add a range of 19 standard, custom color and logo options and you have the ultimate in beastly beauty.

PRODUCT INFORMATION

- 1" x 24" x 24" Interlocking (Dowel) Tile System
(Complete system US patent pending)
- Prefabricated factory molded tile consisting of 100% recycled SBR rubber backing and either recycled SBR or EDPM top wearlayer. Waffle bottom design for shock absorption, impact adsorption, drainage and cable routing.
- Weight: 18lbs per tile
- Manufactured in the USA

REGUPOL® AKTIVPRO™

MODULAR SPORTS & FITNESS SURFACES

REGUPOL® AKTIVPRO™ TILE



33 KEYSTONE DRIVE
LEBANON, PA 17042
P: 1-800-537-8737
F: 717-675-2199
www.regupol.com



COLOR SELECTION (Top Surface Pattern/Wearlayer)

Choose from manufacturer's 19 standard colors or custom color blends based on standard color granule availability. Minimum orders apply for custom colors.

PHYSICAL TESTING (ASTM)

Density ASTM D3676 (top layer)	65 pcf - 80 pcf (depends on surface color)
Hardness ASTM D2240 (Shore A)	65 +/- 5
Tear Strength ASTM D624	70 pli min
Elongation ASTM D412	> 150%
Tensile Strength ASTM D412	> 200 PSI
Resistance to Chemicals ASTM F925	No Change
Coefficient of Friction ASTM D2047	> 0.95
Impact Insulation Class (IIC) E492	> 50
ASTM E648 Critical Radiant Flux	Class II
LEED Points	Can contribute up to six LEED Credits

PRODUCT INSTALLATION

Product can be loose laid indoors over a compacted base or existing floorcovering using the interlocking molded dowel pin system. Each tile contains six barbed dowels to secure the tile in place. Dowels are inserted into factory molded dowel holes and the tiles are driven together using a wooden block or mallet.

WARRANTY

Regupol America (the "Seller") warrants that its Regupol AktivPro (the "Product") shall conform to all published specifications, and to any specifications required by Buyer and accepted by Seller, for a period of ten (10) years from the date of shipment. Seller warrants that, during the warranty period, the Product shall not exhibit signs of excessive deterioration, as reasonably determined by Seller. All other warranties, including the warranties of merchantability and fitness for a particular purpose, are expressly excluded. Buyer's sole and exclusive remedy for defective Product, shall be, at Seller's options, repair or replacement of the defective Product. Seller shall not, under any circumstances including, but not limited to, delay in delivery, breach of contract, breach of warranty, negligence, tort, strict liability or use of materials sold by Seller, be liable to Buyer or any other party for any special, incidental, indirect or consequential damages, or for losses of any kind whatsoever. In no event shall Seller's liability for defective Product sold to Buyer exceed the purchase price thereof.